



# SEAMLESS MOBILITY WITH EXCEPTIONAL PERFORMANCE

3 inch POS Printer

## SRP-350plusIII



### HIGHLIGHTS



#### High-quality Printing Performance

- Fast printing up to 300mm/sec (20% faster than the SRP-350plusII)
- Cost-saving paper reduction function (Barcode reduction included)
- 16-step true gray scale printing of graphics
- Proven-reliability as a family of steady-selling SRP-350 line



#### World-class Flexibility

- Compatible with smart device including iOS (MFi optional), Android, and Windows RT 8.1
- Simple-to-use Wifi or Bluetooth wireless printing (optional)
- Built-in USB and Ethernet

#### User-friendly Design

- Anti-jam guide
- Stand-alone or Space-saving wall-mount use
- 2" or 3" paper choice



**BIXOLON**<sup>®</sup>  
a Better Solution for your Business<sup>™</sup>

# 3 inch POS Printer SRP-350plusIII



## SPECIFICATIONS

### Print Characteristics

**Print Method**

Direct Thermal

**Print Speed**

SRP-350plusIII: 300 mm/sec

SRP-352plusIII: 270 mm/sec

**Print Resolution**

SRP-350plusIII: 180 dpi

SRP-352plusIII: 203 dpi

**Print Width**

Up to 72 mm

**Sensor**

Paper End, Paper Near End, Cover Open

### Media Characteristics

**Media Type**

Receipt

**Media Width**

80 mm / 58 mm

**Media Roll Diameter**

Up to 83 mm

**Media Thickness**

0.062 ~ 0.075 mm

**Supply Method**

Easy Paper Loading

### Physical Characteristics

**Dimensions (WxLxD)**

145 x 200 x 146 mm

(5.70 x 7.87 x 5.74 inch)

**Weight**

1.56 kg (3.43 lbs)

**Power**

EnergyStar Certified,

External Power Adaptor 100-240V AV, 50/60Hz

**Drawer Port**

2 ports (via y-type adaptor)

### Performance Characteristics

**Memory**

64 Mbit SDRAM, 32 Mbit FlashROM

**NV Image Memory**

768 Kbytes (mono)

**Receive Buffer**

4 Kbytes

**User Define Buffer**

12 Kbytes

**Interface**

Triple Interface

USB V2.0 FS + Ethernet + Serial / Parallel /

WLAN\* / Bluetooth V2.1+ EDR\*\* / powered USB

\* WLAN: 802.11b/g/n

\*\*Bluetooth: Class 1 (100 m), MFi certified

### Environment Characteristics

**Temperature**

Operating: 0 ~ 45°C (32 ~ 113°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

**Humidity**

Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

### Reliability

**Printer Unit (MCBF)**

70 Million Lines

**Thermal Print Head (TPH)**

150 km

**Auto Cutter**

1.8 Million Cuts

### Software

**Emulation**

BXL / POS

**Driver / Utility**

Windows Driver, OPOS Driver, JPOS Driver,

Linux CUPS Driver, Mac Driver,

Virtual COM USB/Ethernet Driver, Utility Program

**SDK**

iOS SDK, Android SDK, Windows SDK

### Fonts / Graphics / Symbologies

**Character Size**

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24

KOR, CHN, JPN: 24 x 24

**Characters Per Line**

SRP-350plusIII: Font A: 42 Font B, C: 56

KOR, CHN, JPN: 21

SRP-352plusIII: Font A: 48 Font B, C: 64

KOR, CHN, JPN: 24

**Character Sets**

Alphanumeric: 95

Extended Graphics: 128 x 37 page

International: 32

**Graphics**

Supporting user-defined fonts, graphics, formats, and logos

**Barcode Symbologies**

1D: Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E

2D: Data Matrix, PDF417, QR code

BR-SRP-350plusIII-EN-APR14

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

**BIXOLON®**

www.bixolon.com

**BIXOLON Co., Ltd.**

7~8F, (Sampyeong-dong), 20, Pangyoyeok-ro241beon-gil,  
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

**BIXOLON America Inc.**

3171 Fujita St Torrance,  
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

**BIXOLON Europe GmbH**

Tiefenbroicher Weg 35,  
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de